

Żuraw przeznaczony dla wózków widłowych



SPECYFIKACJA

CHARAKTERYSTYKA

1.1	Typ		1000	1500	2000	2500	5000	8000
1.2	Hak		Obrotowy	Obrotowy	Obrotowy	Obrotowy	Obrotowy	Obrotowy
1.3	Spadek udźwigu 800 mm	[kg]	1000	1500	2000	2500	5000	8000
1.4	Spadek udźwigu 1000 mm	[kg]	500	750	1000	1250	2500	400
1.5	Spadek udźwigu 1200 mm	[kg]	325	500	650	825	1650	2650
1.6	Spadek udźwigu 1400 mm	[kg]	250	375	500	625	1250	2000
1.7	Spadek udźwigu 1600 mm	[kg]	200	300	400	500	1000	1600
1.8	Spadek udźwigu 1800 mm	[kg]	165	250	325	400	825	1325
1.9	Spadek udźwigu 2000 mm	[kg]	140	200	275	350	700	1125

WYMIARY

2.1	Dystans pomiędzy widłami A	[mm]	300	300	300	300	300	300
2.2	Wymiary wideł B x C	[mm]	200 x 80	200 x 80	200 x 80	200 x 80	200 x 80	200 x 80
2.3	Długość wysięgnika L max	[mm]	2200	2200	2200	2200	2200	2200

WAGA

3.1	Udźwig	[kg]	1000	1500	2000	2500	5000	8000
3.2	Waga	[kg]	60	75	95	110	145	185

