COUNTERBALANCED

4-wheel engine trucks torque converter







M315 - 318

1.5 t - 1.8 t

<u>↑</u> 6970 mm

M320 - 325 2.0 t - 2.5 t

<u>↑</u> 6970 mm blesel/LPG

M330 - 335

3.0 t - 3.5 t <u>↑</u> 6970 mm

4-wheel engine trucks hydrostatic







Drago 150 - 180 - 200

1.5 t - 1.8 t - 2.0 t

<u>↑</u> 6170 mm

2.5 t - 3.0 t - 3.5 t

<u>↑</u> 7960 mm

<u>↑</u> 7960 mm

blesel/LPG

Drago 400 - 450 - 500

4.0 t - 4.5 t - 5.0 t

<u>↑</u> 6650 mm

DIESEL

Drago E 250 - 300- 350

2.5 t - 3.0 t - 3.5 t

























CESAB PRODUCT RANGE

Counterbalanced and Warehouse Equipment











COUNTERBALANCED

3-wheel electric trucks



BIT 800 - 1000 - 1200

@ | 0.8 t − 1.0 t − 1.2 t 5965 mm

24V / 800 Ah



24V / 1000 Ah

B315 - 316 - 316L - 318 - 318L - 320

1.5t-1.6t-1.8t-2.0t <u>↑</u> 7470 mm

48V / 750 Ah

WAREHOUSE EQUIPMENT

Hand pallet trucks



CE200 - 230 - 300

2.0 t - 2.3 t - 3.0 t

The 2.3 t model is also available with low forks, quicklift feature and handbrake. Low forks are standard on the 2.0 t model.



CE200ST

2.0 t

Stainless steel



CE100HL - 100HLE

1.0 t

<u>↑</u> 810 mm

 Manual and electric scissor lifters.

Powered stacker trucks



1580 mm

24 V / 230 Ah

€ | 0.8 t

2000 mm 24 V / 63 Ah

S110 - 110S

1.0t

S110S: straddle support arm



S210 - 212 - 214

Can lift up to 2000 kg when lifting with

the support arms only. Available with

optional automatic height adjustment.

24V / 300 Ah

1.0t - 1.2t - 1.4t

4755 mm

 Straddle support arms. Optional operator platform available. Optional operator platform

S212S

RG | 1.2 t

<u>↑</u> 4755 mm

24 V / 300 Ah

also available.

4-wheel electric trucks



B415 - 416 - 416L - 418 - 418L - 420

6 | 1.5t-1.6t-1.8t-2.0t <u>↑</u> 7470 mm

48V / 750 Ah



B620 - 625 - 625L - 630 - 630L - 635

2.0t - 2.5t - 3.0t - 3.5t <u>↑</u> 6500 mm

80V / 700 Ah



Mak 400 - 450 - 500 4.0 t - 4.5 t - 5.0 t

<u>↑</u> 7450 mm

80V / 775 Ah

Powered pallet trucks



뎶 | 1.3 t

24V / 63 Ah

Reach trucks



P214 - 216 - 218 - 220 - 225

1.4t - 1.6t - 1.8t - 2.0t - 2.5t

24V / 300 Ah

Optional operator platform available



P320 - 324

2.0t - 2.4t

24V / 620 Ah

The P320 is also available as a high performance version (8.5 km/h). The P324 is also available with power steering.



24V / 300 Ah

Elevating support arms. Optional

S220D 🚾 | 1.0t

2100 mm

24 V / 300 Ah

Double stacker, lifts 800 + 1200 kg lifting Also available as a walkie version (without platform and longer tiller arm). with forks + support arms or 2000 kg when lifting with the support arms only.

Optional operator platform available.

5400 mm

24V / 425 Ah

S313 - 316 - 320 S313L - 316L - 320L 1.25t - 1.6t - 2.0t

1.25t - 1.6t - 2.0t 5400 mm

24V / 425 Ah

 Elevating support arms. Also available as a walkie version (without platform and longer tiller arm).

Compact electric trucks



cenTAURO 48 160L - 200L

№ | 1.6 t - 2.0 t 6970 mm

48V / 840 Ah



cenTAURO 80 250 - 300

<u>↑</u> 6860 mm

80V / 735 Ah

2.5 t - 3.0 t

<u>↑</u> 6450 mm 80V / 1250 Ah

B860 - 870 - 885

Heavy duty electric truck



6.0 t - 7.0 t - 8.5 t

8500 mm 48 V / 620 Ah

 Also available as a cold store version as well as drive-in version with narrow overhead guard.

R212 - 214 - 216

1.2t - 1.4t - 1.6t

1.4t - 1.6t - 1.8t - 2.0t - 2.5t

12500 mm 48V / 930 Ah

 Also available as a cold store version, with or without heated cabin, as well as a drive-in version with narrow overhead guard.

Also available as a walkie version.

1	Legend		
KG	Rated capacity	0	Additional info
<u> 1</u>	Maximum lifting height	•	Fuel type
	Maximum battery capacity	← N	Nominal draw-bar pu

S212L-214L 1.2 t - 1.4 t 4755 mm





🔓 | 1.35 t

5400 mm

24V / 425 Ah

Adjustable straddle support arms. (Without platform and longer tiller arm.)